

XTC COMPOSITE 29ER

THE QUICK, SHARP FEEL OF A SUPERLIGHT COMPOSITE HARDTAIL, THE CONTROL OF 29-INCH WHEELS. XC RACERS CAN HAVE IT ALL.



SPECIFICATIONS

FRAME	
SIZES	S, M, L, XL
COLORS	Composite/Blue
FRAME	Giant Composite Technology
FORK	Fox F29 FIT RLC w/ 15QR Thru-Axle and OverDrive Steerer, 100mm Travel
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact, Flat 31.8
STEM	Giant Contact
SEATPOST	Giant Contact, 30.9
SADDLE	Fizik Tundra 2 w/ Kium Rails
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM X9, 2x10 Speed
FRONT DERAILLEUR	SRAM X9
REAR DERAILLEUR	SRAM XO
BRAKES	Avid Elixir R, 160mm
BRAKE LEVERS	Avid Elixir R
CASSETTE	SRAM PG 1070 12x36, 10-Speed
CHAIN	SRAM PC1071
CRANKSET	SRAM X9, 26/39
BOTTOM BRACKET	SRAM GXP Press Fit
WHEELS	
RIMS	Giant P-XC29 2
HUBS	[F] Giant Tracker w/ 15mm Axle, [R] Giant Tracker P-XC series, 32h
SPOKES	DT Swiss Competition 14/15g, w/ Alloy Nipples
TIRES	Schwalbe Racing Ralph, 29x2.10 EVO Folding TL Ready

FRAME DESIGN

Giant's first-ever composite 29er was developed to meet the demands of our professional racers. They asked for the stability and control of a 29er, but with razor-sharp handling. Made with Giant Composite Technology, the frame's massive MegaDrive downtube and OverDrive headtube give it quick, precise steering. Asymmetrical chainstays and a PowerCore bottom bracket boost traction and acceleration. Find new confidence, and speed, with Xtc Composite 29er.



FEATURES

KEY UPGRADES (OVER XTC COMPOSITE 29ER 1):

- Fox 32 F29 RLC-100, QR15 thru-axle, tapered steerer fork
- SRAM X0/X9 componentry
- Giant Contact stem, seatpost
- Avid Elixir R hydraulic disc brakes
- Sizes: S, M, L, XL
- Color: Composite/Blue

U.S. Average Retail Price: \$3,675

GEOMETRY

Size	Part number	Head Angle	Seat Angle	Top Tube	Reach	Head Tube	Stack	Chain Stay	Wheel Base	Standover Height
Inches		Degree	Degree	Inches	Centim..	Inches	Centim..	Inches	Inches	Inches
S/16	333693	71	73	22.6	N/A	4.1	N/A	17.3	41.8	28.5
M/18	333694	71.5	72.5	23.4	N/A	4.1	N/A	17.3	42.1	29.6
L/20	333695	71.5	72	24.2	N/A	4.3	N/A	17.3	42.7	30.5
XL/22	333696	71.5	72	25	N/A	4.7	N/A	17.3	43.5	31.6