



SPECIFICATIONS / SPECIFICATIONS

FRAME	SIZES / TAILLES	XS, S, M, L
	COLOURS / COULEURS	Green/ Aluminum/ White
	FRAME / CADRE	ALUXX SL-Grade Aluminum
COMPONENTS	FORK / FOURCHE	Advanced-Grade Composite/ Alloy OverDrive Steerer
	SHOCK / AMORTISSEUR	N/A
	HANDLEBAR / CINTRE	Giant 6061 Al Wmn's Anatomic, 31.8mm
	STEM / POTENCE	Giant 3D Forged 6061 Al, 31.8mm, 6 deg
	SEATPOST / TIGE DE SELLE	Giant Composite, 30.9x370mm
DRIVETRAIN	SADDLE / SELLE	Giant Racing Women's
	PEDALS / PÉDALES	Crank Brothers Smarty
	SHIFTERS / MANETTES	Shimano R700, short reach, 10SPD
	FR DÉRAILLEUR / DÉRAILLEUR AV.	Shimano 10S
	RR DÉRAILLEUR / DÉRAILLEUR AR.	Shimano 10S
	BRAKES / FREINS	Shimano 10S
	BRAKE LEVERS / MANETTES DE FREIN	Shimano R700, short reach
	CASSETTE / CASSETTE	Shimano 10S, 12-27T, 10SPD
	CHAIN / CHAÎNE	Shimano 10S
	CRANKSET / PÉDALIER	FSA Gossamer, 30/39/50T
WHEELS	BOTTOM BRACKET / BOÎTER DE PÉDALIER	FSA Mega EXO, external
	RIMS / JANTES	Mavic CXP22, F: 24H/ R: 28H
	HUBS / MOYEURS	Formula, alloy, sealed
	SPOKES / RAYONS	14G Sapim Race
	TIRES / PNEUS	Kenda Kriterium, 700x25C
	EXTRAS	



FEATURES / CARACTERISTIQUES

- Shimano 10-speed 10S component group, FSA Gossamer triple crankset
- Crank Brothers Smarty pedals, Giant Racing women's saddle
- Wheelset: Mavic CXP22 rims, Formula sealed hubs, SAPIM race spokes

FRAME GEOMETRY / GEOMETRIE DU CADRE

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters	Green/ Aluminum/ White	degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	296922	71.0	74.5	51.0	13.0	42.0	98.3	28.9
S/46.5 cm	296923	72.0	74.0	52.5	15.0	42.0	98.5	29.6
M/50.0 cm	296924	72.5	73.5	54.0	17.5	42.0	99.0	30.6
L/53.5 cm	296925	72.5	73.0	55.5	19.0	42.0	100.0	31.0

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire