

## TCR ADVANCED SL 1



## SPECIFICATIONS / SPECIFICATIONS

FRAME	SIZES / TAILLES	XS,S,M,M/L,L,XL
	COLOURS / COULEURS	Composite/Team Blue
	FRAME / CADRE	Advanced SL-Grade Composite, Integrated Seatpost
	FORK / FOURCHE	Advanced SL-Grade Composite, Full Composite OverDrive Steer
	SHOCK / AMORTISSEUR	N / A
COMPONENTS	HANDLEBAR / CINTRE	Race Face Revolution 31.8mm
	STEM / POTENCE	Race Face Revolution 31.8mm, 6 deg
	SEATPOST / TIGE DE SELLE	Advanced SL-Grade Composite, Integrated Design
	SADDLE / SELLE	Fi'zi:k Arione CX w / kium rails
	PEDALS / PEDALES	Not Included
DRIVETRAIN	SHIFTERS / MANETTES	Shimano Dura-Ace 7900
	FR DERAILLEUR / DERAILLEUR AV.	Shimano Dura-Ace 7900
	RR DERAILLEUR / DERAILLEUR AR.	Shimano Dura-Ace 7900
	BRAKES / FREINS	Shimano Dura-Ace 7900
	BRAKE LEVERS / MANETTES DE FREIN	Shimano Dura-Ace 7900
	CASSETTE / CASSETTE	Shimano Ultegra 12-25T 10SPD
	CHAIN / CHAÎNE	Shimano Dura-Ace 7900
	CRANKSET / PEDALIER	Shimano Dura-Ace 7900 39/52T
	BOTTOM BRACKET / BOÎTER DE PEDALIER	Shimano Dura-Ace, Internal Press Fit
WHEELS	RIMS / JANTES	Mavic Ksyrium SL Premium
	HUBS / MOYEUX	Mavic Ksyrium SL Premium
	SPOKES / RAYONS	Mavic Ksyrium SL Premium
	TIRES / PNEUS	Michelin Pro Race3 700x23C
	EXTRAS	2 ISP Clamps - Reg 20mm/XL 40mm



## FEATURES / CARACTERISTIQUES

- Complete Shimano Dura-Ace 7900-series component group
- Race Face Revolution handlebar and stem, Integrated seatpost
- Mavic Ksyrium SL Premium wheelset, Michelin Pro Race 3 tires

## FRAME GEOMETRY / GEOMETRIE DU CADRE

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	299401	71.0	74.5	52.0	12.0	40.5	97.7	28.5
S/46.5 cm	299402	72.0	73.5	53.5	13.5	40.5	97.4	29.2
M/50.0 cm	299403	73.0	73.0	55.5	15.0	40.5	98.0	30.1
M/L/53.5 cm	299404	73.0	72.0	57.0	17.0	40.5	98.6	31.0
L/55.5 cm	299405	73.0	72.0	58.5	18.5	40.5	100.1	31.7
XL/58.5 cm	299406	73.0	72.0	60.5	20.0	40.5	102.1	32.4

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire