

TRINITY 0

YOU'RE UP BEFORE THE SUN, STICKING TO THE TRAINING PLAN. RUNNING, SWIMMING, RIDING. COUNT ON TRINITY TO HANDLE THE RIDING PART.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,L
	COLORS	Black/White/Blue
	FRAME	ALUXX SL-Grade Aluminum, Aero Design
	FORK	Advanced-Grade Composite, Alloy Steerer
SHOCK	N / A	
COMPONENTS	HANDLEBAR	Giant Connect SL 31.8 base bar w/ Vision TriMax clip on
	STEM	Giant Connect SL
	SEATPOST	Giant Alloy Aero, 3 position Fore-Aft
	SADDLE	Giant Unity Performance TRI, Men's
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano Dura-Ace TT
	FRONT DERAILLEUR	Shimano 105
	REAR DERAILLEUR	Shimano Ultegra 6700
	BRAKES	Shimano 105
	BRAKE LEVERS	Giant Trinity - aluminum
	CASSETTE	Shimano 105 11x23, 10-speed
	CHAIN	Shimano 105
	CRANKSET	FSA Gossamer MegaExo Time Trial, 42/53
BOTTOM BRACKET	FSA Mega Exo, External	
WHEELS	RIMS	Giant Alloy SL Aero 42mm
	HUBS	Formula Sealed Bearing, 16/20h
	SPOKES	SAPIM Race, 14/15g
	TIRES	Michelin Lithion2, 700x23 Folding
	EXTRAS	Saddle Two bottle cage holder

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

With its Compact Aero Road Design, aerodynamic profile and super-efficient pedaling performance, Trinity is the ticket to your fastest time yet. Built around a lightweight ALUXX SL aluminum frame and featuring a steep seattube for an aggressive yet comfortable stance, Trinity is the fastest way to get faster.



KEY UPGRADES (FROM TRINITY 1)

- 10-speed Shimano 105 shifting, brakeset
- Giant Connect SL stem
- Shimano Ultegra 6700 rear derailleur, Michelin Lithion 2 tires

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS 43.0	388652	72.0	78.0	50.5	10.0	39.0	97.0	28.2
S 46.5	388653	72.0	78.0	52.0	11.5	39.0	98.6	29.0
M 50.0	388654	72.5	78.0	54.0	13.0	39.0	100.4	29.6
L 55.0	388655	72.5	78.0	56.5	14.5	39.0	103.0	30.7

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire