

ANTHEM ADVANCED

MOUNTAIN COMPETITION

Adam Craig asked for three qualities in his ultimate XC race rig: outright speed, razor-sharp handling and ultra light weight. Giant responded by building him the revolutionary Anthem Advanced. Giant's own formulaOne Composite construction and legendary Maestro Suspension are teamed up in the world's premier full-composite, full-suspension XC racing frameset.



SPECIFICATIONS

FRAME	SIZES	XS, S, M, L, XL
	COLORS	Team Blue/White
	FRAME	formulaOne Composite, 3.5" Maestro Suspension
	FORK	Fox 32 F80RLC, 80mm travel
	SHOCK	Fox Float RP23
COMPONENTS	HANDLEBAR	Race Face Next SL low rise, 31.8
	STEM	Race Face Deus SL, 31.8
	SEATPOST	Race Face Next SL 400x 30.9mm
	SADDLE	WTB Silverado SLT Ti
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano XTR Rapidfire
	FRONT DERAILLEUR	Shimano XTR
	REAR DERAILLEUR	Shimano XTR, top normal
	BRAKES	Shimano XTR 160F/140R
	BRAKE LEVERS	Shimano XTR
WHEELS	CASSETTE	Shimano XTR 11/34, 9-speed
	CHAIN	Shimano Dura-Ace
	CRANKSET	Shimano XTR, 22/32/44
	BOTTOM BRACKET	Shimano XTR, external
	RIMS	Shimano XTR
HUBS	Shimano XTR, Centerlock	
SPOKES	Shimano XTR	
TIRES	Michelin XC Dry ² , 26x2.0 folding	
EXTRAS		

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Featuring a breakthrough full-composite, cross-country racing suspension frameset, the Anthem Advanced is the lightest and most compliant off-road frame Giant has ever produced. Using hyper-light T-800 formulaOne Composite frame material and composite Maestro Suspension rocker links, this featherweight frame offers unparalleled ride quality and performance.



FEATURES

- Inertia valve-equipped Fox 32 F80RLC, 80mm suspension fork, and Fox Float RP23 rear shock
- Complete Shimano XTR group
- Race Face Next composite handlebar and seatpost
- Super-light new Shimano XTR racing wheelset

FRAME GEOMETRY

Actual Frame Size	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
inches	degrees	degrees	inches	inches	inches	inches	inches
XS/14.5	72.0	74.0	21.9	4.6	16.7	40.7	30.2
S/16	72.0	73.5	22.6	4.6	16.7	41.3	30.4
M/18	72.0	73.0	23.4	5.1	16.7	41.9	31.0
L/20	72.0	73.0	24.2	5.7	16.7	42.7	32.1
XL/22	72.0	72.5	25.0	6.3	16.7	43.3	32.6

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire