

FCR 3

ROAD FITNESS

For the athlete who realizes there's more to fitness than a rack of barbells, a treadmill and a TV. An ALUXX aluminum-framed FCR gets you out of the gym and onto the open road.



SPECIFICATIONS

FRAME	SIZES	XS, S, M, L, XL
	COLORS	Black/Brushed
	FRAME	ALUXX Aluminum, Compact Road Design
	FORK	CroMo Steel
	SHOCK	N / A
COMPONENTS		
	HANDLEBAR	6061AL lowrise
	STEM	6061AL adjustable
	SEATPOST	Aluminum
	SADDLE	WTB Laser V Comp
	PEDALS	Steel Cage
DRIVETRAIN		
	SHIFTERS	Shimano STR-221
	FRONT DERAILLEUR	Shimano R443
	REAR DERAILLEUR	Shimano Altus
BRAKES		
	BRAKES	TB-07AL
	BRAKE LEVERS	Shimano STR-221
	CASSETTE	SRAM PG 830 11/28, 8-speed
	CHAIN	KMC Z72
	CRANKSET	RPM CFM Triple, 30/39/50
	BOTTOM BRACKET	BB 7420
WHEELS		
	RIMS	CR06
	HUBS	Alloy Sealed Bearing
	SPOKES	Stainless Steel
	TIRES	Kenda Kwest, 700x32
	EXTRAS	

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Featuring a butted ALUXX aluminum frame and formulaOne Composite fork, FCR geometry delivers equal parts performance and sure-footed positioning for spirited workout rides or confident commuting.



FEATURES

- Wide-range 8-speed Shimano shifting with RPM triple crankset
- Comfortable WTB Laser V Comp saddle
- Confidence-inspiring Kenda Kwest 700x32c tires

FRAME GEOMETRY

Actual Frame Size	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters	degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0	71.0	75.0	52.5	12.5	42.5	100.9	29.5
S/46.5	72.0	74.0	54.5	14.5	42.5	101.0	30.3
M/50.0	72.5	73.0	56.5	17.0	42.5	102.5	31.3
L/55.5	72.5	73.0	58.5	20.0	42.5	103.5	32.8
XL/58.5	72.5	72.5	60.5	22.5	42.5	104.9	33.7

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire