

TCR C1

ROAD COMPETITION

When you're ready to give it your all, TCR Composite is ready to respond. Featuring formulaOne Composite construction for responsive handling in an astonishingly lightweight frame. Built by hand in Giant's C-Tech factory and ridden to victory the world over.



SPECIFICATIONS

FRAME	SIZES	XS, S, M, M/L, L, XL
	COLORS	Silver/Composite
	FRAME	formulaOne Composite, Compact Road Design
	FORK	formulaOne Full Composite
	SHOCK	N / A
COMPONENTS		
	HANDLEBAR	Race Face Revolution, 31.8
	STEM	Race Face Revolution, 31.8
	SEATPOST	formulaOne Composite
	SADDLE	Fi'zi:k Arione w / kium rails
	PEDALS	Not Included
DRIVETRAIN		
	SHIFTERS	Shimano Ultegra SL
	FRONT DERAILEUR	Shimano Ultegra SL
	REAR DERAILEUR	Shimano Ultegra SL
	BRAKES	Shimano Ultegra SL
	BRAKE LEVERS	Shimano Ultegra SL
	CASSETTE	Shimano Ultegra 12/25, 10-speed
	CHAIN	Shimano Ultegra
	CRANKSET	Shimano Ultegra SL, 39/53
	BOTTOM BRACKET	Shimano Ultegra, external
WHEELS		
	RIMS	Mavic Ksyrium Elite
	HUBS	Mavic Ksyrium Elite
	SPOKES	Mavic Ksyrium Elite
	TIRES	Michelin Pro Race ³ , 700x23
	EXTRAS	

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Building upon its six-year heritage, the TCR Composite features additional weight reduction and increased lateral stiffness made possible only through Giant's proprietary formulaOne Composite manufacturing process.



FormulaOne
COMPOSITE TECHNOLOGY

KEY UPGRADES (OVER TCR C2)

- New Ultegra SL drivetrain
- Race Face Revolution handlebar and stem
- Lightest Mavic Ksyrium Elite wheelset

FRAME GEOMETRY

Actual Frame Size	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters	degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0	71.0	74.5	52.0	12.0	40.5	97.7	28.5
S/46.5	72.0	73.5	53.5	13.5	40.5	97.4	29.3
M/50.0	73.0	73.0	55.5	15.0	40.5	98.0	30.1
M/L/53.5	73.0	72.5	57.0	17.0	40.5	99.2	31.1
L/55.5	73.0	72.5	58.5	18.5	40.5	100.6	31.7
XL/58.5	73.0	72.0	60.5	20.0	40.5	102.1	32.2

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire