

# TRANCE ADVANCED

## MOUNTAIN TRAIL

The definitive trail bike for riders who take their singletrack seriously. Featuring a breakthrough full formulaOne Composite full-suspension frameset with composite Maestro rocker links and 4.2 inches of travel. Saves precious grams and adds superior ride compliance so you can hammer away, all day.



### SPECIFICATIONS

FRAME	SIZES	XS, S, M, L, XL
	COLORS	Black Gold
	FRAME	formulaOne Composite, 4.2" Maestro Suspension
	FORK	Fox 32 F100RLC, 100mm travel
	SHOCK	Fox Float RP23
COMPONENTS		
	HANDLEBAR	Race Face Next SL low rise, 31.8
	STEM	Race Face Deus SL, 31.8
	SEATPOST	Race Face Next SL 400x30.9mm
	SADDLE	WTB Devo Carbon w/Ti rails
	PEDALS	Not Included
DRIVETRAIN		
	SHIFTERS	SRAM X.0 trigger
	FRONT DERAILLEUR	Shimano XTR
	REAR DERAILLEUR	SRAM X.0
	BRAKES	Avid Juicy carbon 160F/160R
	BRAKE LEVERS	Avid Carbon
	CASSETTE	Shimano XTR 11/34, 9-speed
	CHAIN	Shimano Dura-Ace
	CRANKSET	Shimano XTR, 22/32/44
	BOTTOM BRACKET	Shimano XTR, external
WHEELS		
	RIMS	Mavic CrossMax SL
	HUBS	Mavic CrossMax SL
	SPOKES	Mavic CrossMax SL
	TIRES	Kenda Nevegal, 26x2.1 folding
	EXTRAS	

Specifications and availability subject to change without notice.

### FRAME TECHNOLOGY

Featuring a full composite, trail-specific suspension frameset, the Trance Advanced saves precious grams and adds superior ride compliance through its formulaOne Composite frame and composite Maestro rocker links.

**formulaOne**  
COMPOSITE TECHNOLOGY

**MAESTRO**  
SUSPENSION

### FEATURES

- Full-featured Fox 32 F100RLC, 100mm suspension fork and Fox Float RP23 rear shock
- High-end SRAM X.0 shifters/rear derailleur with Shimano XTR crankset
- Lightweight Race Face Next SL composite handlebar and seatpost
- Lightest Mavic CrossMax SL wheelset

### FRAME GEOMETRY

Actual Frame Size	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
inches	degrees	degrees	inches	inches	inches	inches	inches
XS/14.5	70.5	73.5	21.4	4.6	17.0	41.1	30.5
S/16	70.5	73.5	22.1	4.6	17.0	41.8	30.2
M/18	70.5	73.5	23.0	5.0	17.0	42.7	30.6
L/20	70.5	73.5	23.7	5.9	17.0	43.7	31.6
XL/22	70.5	73.5	24.6	6.9	17.0	44.5	32.5

\*Seat angle is effective

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire