

## DEFY 3

It's a new year, and an all-new Defy. Race-inspired engineering with an all-new tubeset from the world leader in aluminum technology. Defy is lighter to help with the climbs, stiffer to maximize power transfer and just plain faster than its closest competitor.



## SPECIFICATIONS

FRAME	SIZES	XS,S,M,M/L,L,XL
	COLORS	Blue/Silver/Black
	FRAME	ALUXX SL-Grade Aluminum
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
COMPONENTS	SHOCK	N / A
	HANDLEBAR	Giant Alloy Anatomic Bend, 26.0
	STEM	Giant Alloy 4-bolt
	SEATPOST	Giant Alloy, 30.9
DRIVETRAIN	SADDLE	Giant Performance Road, Men's
	PEDALS	Caged w/ Clips
	SHIFTERS	Shimano 2200
	FRONT DERAILLEUR	Shimano 2203
WHEELS	REAR DERAILLEUR	Shimano Sora
	BRAKES	Tektro R350 Dual Pivot
	BRAKE LEVERS	Shimano 2200, short reach
	CASSETTE	SRAM PG 850 11/26, 8-speed
EXTRAS	CHAIN	KMC Z7
	CRANKSET	FSA Vero, 30/42/52
	BOTTOM BRACKET	Cartridge
	RIMS	Alex DA-22, Double Wall
	HUBS	Formula 32H
	SPOKES	Stainless
	TIRES	Kenda Kriterium, 700x25

Specifications and availability subject to change without notice.

## FRAME TECHNOLOGY

Ride like a pro on the most advanced ALUXX SL aluminum frame yet. Giant flexes some engineering muscle to produce a lighter, stiffer tubeset than before, with better ride tuning, so you get the best of everything.



## FEATURES

- 8-speed Shimano shifting with Sora rear derailleur
- Composite fork with OverDrive steerer
- Alex rims, Formula hubs/stainless spokes wheelset with Kenda Kriterium Tires

## FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	382552	71.0	74.0	51.5	12.5	42.0	98.3	29.0
S/46.5 cm	382553	72.0	74.0	53.0	14.5	42.0	99.0	29.7
M/50.0 cm	382554	72.5	73.0	54.5	16.5	42.0	99.0	30.6
M/L/53.5 cm	382555	72.5	73.0	56.0	18.5	42.0	100.5	31.1
L/55.5 cm	382556	72.5	72.0	57.5	20.5	42.0	100.8	32.0
XL/58.5 cm	382557	72.5	72.0	59.5	22.5	42.0	102.8	32.8

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire