

AERYN 1

A TRI[®] BIKE HAS TWO OBJECTIVES: MOTIVATE YOU AND MAKE YOU FASTER. AERYN MAKES TRAINING MORE FUN—WHICH IN TURN IMPROVES YOUR TIME.



SPECIFICATIONS

FRAME	SIZES	XS,S,M
	COLORS	Green/White/Black
	FRAME	ALUXX SL-Grade Aluminum, Aero Design
	FORK	Advanced-Grade Composite, Alloy Steerer
SHOCK	N / A	
COMPONENTS	HANDLEBAR	Alloy base bar w/ Vision TriMax clip on, 31.8
	STEM	Giant Connect
	SEATPOST	Giant Trinity Alloy Aero
	SADDLE	Giant TRI Women's
PEDALS	Not Included	
DRIVETRAIN	SHIFTERS	Shimano 9-speed, bar end
	FRONT DERAILLEUR	Shimano Sora
	REAR DERAILLEUR	Shimano Sora
	BRAKES	Tektro Giant specific TK-R710, Dual Pivot
	BRAKE LEVERS	Giant Trinity, alloy
	CASSETTE	SRAM PG950 11x26, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	FSA Vero, 39/53
BOTTOM BRACKET	FSA Cartridge	
WHEELS	RIMS	Giant SL Aero 42mm
	HUBS	Formula Sealed Bearing, 16/20h
	SPOKES	SAPIM Race, 14/15g
	TIRES	Kenda Kriterium, 700x23
	EXTRAS	Saddle Two bottle cage holder

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Stiff enough to put your power straight to the pedals, balanced enough to keep you comfortable during long training efforts, and aero[®] enough to shave seconds off your time—that's Aeryn. Made with super-light ALUXX SL frame tubing, it's your new best friend against the clock or the competition.



FEATURES

- 9-speed Shimano Sora components
- Giant Connect stem, Vision clip-on
- Giant TRI women's saddle

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS 43.0	388352	72.0	78.0	50.5	11.5	39.0	97.1	28.2
S 46.5	388353	72.0	78.0	51.5	12.5	39.0	98.2	29.0
M 50.0	388354	72.5	78.0	53.5	14.0	39.0	100.0	29.6

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire