

AVAIL ADVANCED 2

CRANKING MAXIMUM SPEED IS ONE THING. STAYING STRONG OVER THE LONG HAUL IS ANOTHER. NOW YOU CAN DO BOTH. COMFORTABLY.



SPECIFICATIONS

FRAME	SIZES	XS,S,M
	COLORS	White/Silver
	FRAME	Advanced-Grade Composite
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Connect SL, Giant for Women, 31.8
	STEM	Giant Connect SL
	SEATPOST	Giant Vector Composite
	SADDLE	Selle Royal Seta W
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano R700, short reach
	FRONT DERAILLEUR	Shimano 105
	REAR DERAILLEUR	Shimano 105
	BRAKES	Tektro Giant specific TK-R710, Dual Pivot
	BRAKE LEVERS	Shimano R700, short reach
	CASSETTE	Shimano 105 12x25, 10-speed
	CHAIN	Shimano 105
	CRANKSET	FSA Gossamer MegaExo, 34/50
	BOTTOM BRACKET	FSA Mega Exo, Internal Press Fit
	WHEELS	RIMS
HUBS		Formula Sealed Cartridge Bearing, 24/28h
SPOKES		SAPIM Race, 14/15g
TIRES		Michelin Lithion 2, 700x25 Folding
EXTRAS		

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Like any professional road-racing bike, the Advanced-grade, aero-sculpted composite Avail Advanced frameset is engineered to go fast. But the silky-smooth feel and thoughtfully designed endurance geometry will keep you riding stronger, longer.



FEATURES

- 10-speed Shimano 105 derailleurs with compact FSA Gossamer crankset
- Lightweight aluminum Giant Connect SL, women's specific handlebar and stem
- Mavic CXP22 wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS 43.0	345252	71.0	74.5	51.0	13.0	42.0	98.3	29.0
S 46.5	345253	72.0	74.0	52.5	15.0	42.0	98.5	29.8
M 50.0	345254	72.5	73.5	54.0	17.5	42.0	99.0	30.7

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire