

AVAIL ALLIANCE

CENTURIES, WEEKEND GROUP RIDES OR QUICK SOLO TRAINING SESSIONS. NO NEED TO CHOOSE JUST ONE WAY TO GO FAST.



SPECIFICATIONS

FRAME	SIZES	XS,S,M
	COLORS	Teal/Composite/White
	FRAME	Alliance Composite/Aluminum Technology
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
SHOCK	N / A	
COMPONENTS	HANDLEBAR	Giant Connect, Giant For Women, 31.8
	STEM	Giant Connect
	SEATPOST	Giant Connect SL Composite, 30.9
	SADDLE	Selle Royal Seta W
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano Tiagra, reach adjust
	FRONT DERAILLEUR	Shimano Tiagra
	REAR DERAILLEUR	Shimano Tiagra
	BRAKES	Tektro Giant specific TK-R710, Dual Pivot
	BRAKE LEVERS	Shimano Tiagra, reach adjust
	CASSETTE	Shimano HG50 12x25, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	Shimano Tiagra, 34/50
	BOTTOM BRACKET	Shimano Internal
WHEELS	RIMS	Mavic CXP22
	HUBS	Formula Sealed Cartridge Bearing, 24/28h
	SPOKES	SAPIM Race, 14/15g
	TIRES	Kenda Kriterium, 700x25
	EXTRAS	

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

The lightweight feel of aluminum combined with the stiffness and sweet riding characteristics of composite frame technology. Avail Alliance gives you both. The result is incredible acceleration, precise handling and a comfortable ride.



Alliance
technology



FEATURES

- 9-speed Shimano Tiagra shifting
- Giant Connect SL composite seatpost, Selle Royal Seta W saddle
- Mavic CXP22 wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS 43.0	383952	71.0	74.5	51.0	13.0	42.0	98.3	29.1
S 46.5	383953	72.0	74.0	52.5	15.0	42.0	98.5	29.7
M 50.0	383954	72.5	73.5	54.0	17.5	42.0	99.0	30.9

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire