

DEFY ADVANCED 1

RIDE FARTHER AND FASTER. LIKE A PLUSH
FIRST-CLASS SEAT ON A SPEEDING BULLET TRAIN.
FAST, EFFICIENT—AND SILKY SMOOTH.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,M/L,L,XL
	COLORS	Composite/White/Silver
	FRAME	Advanced-Grade Composite
	FORK	Advanced-Grade Composite, Full Composite OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Contact, 31.8
	STEM	Giant Contact
	SEATPOST	Giant Vector Composite
	SADDLE	Fi'zi:k Aliante Delta w/ Manganese rails
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano Ultegra 6700
	FRONT DERAILLEUR	Shimano Ultegra 6700
	REAR DERAILLEUR	Shimano Ultegra 6700
	BRAKES	Shimano Ultegra 6700
	BRAKE LEVERS	Shimano Ultegra 6700
	CASSETTE	Shimano Ultegra 6700, 11x28, 10-speed
	CHAIN	Shimano Ultegra 6700
	CRANKSET	Shimano Ultegra 6700, 34/50
	BOTTOM BRACKET	Shimano Dura-Ace, Internal Press Fit
	WHEELS	RIMS
HUBS		Mavic Ksyrium Elite
SPOKES		Mavic Ksyrium Elite
TIRES		Michelin Pro Optimum, 700x25 Folding
EXTRAS		

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

An Advanced-grade composite frame forms the heart of this aero-sculpted beauty. Laid-up by hand, Defy Advanced adds road-smoothing comfort to aggressive racing performance. Whether you're sprinting for primes or launching a long solo break, Defy Advanced is engineered to let you ride farther, faster.



KEY UPGRADES (FROM DEFY ADVANCED 2)

- Complete 10-speed Shimano Ultegra 6700 compact component group
- Lightweight aluminum Giant Contact handlebar and stem
- Lightest Mavic Ksyrium Elite wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS 43.0	384452	71.0	74.0	51.5	12.5	42.0	98.3	29.0
S 46.5	384453	72.0	74.0	53.0	14.5	42.0	99.0	29.8
M 50.0	384454	72.5	73.0	54.5	16.5	42.0	99.0	30.7
M/L 53.5	384455	72.5	73.0	56.0	18.5	42.0	100.5	31.2
L 55.5	384456	72.5	72.0	57.5	20.5	42.0	100.8	31.9
XL 58.5	384457	72.5	72.0	59.5	22.5	42.0	102.8	32.7

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

