

DEFY ADVANCED 0

RIDE FARTHER AND FASTER. LIKE A PLUSH
FIRST-CLASS SEAT ON A SPEEDING BULLET TRAIN.
FAST, EFFICIENT—AND SILKY SMOOTH.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,M/L,L,XL
	COLORS	White/Silver/Blue
	FRAME	Advanced-Grade Composite
	FORK	Advanced-Grade Composite, Full Composite OverDrive Steerer
SHOCK		N / A
COMPONENTS	HANDLEBAR	Giant Contact SLR, Composite, 31.8
	STEM	Giant Contact SLR, Composite
	SEATPOST	Giant Vector Composite
	SADDLE	Fi'zi:k Antares w/ Braided Composite rails
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano Dura-Ace 7900
	FRONT DERAILLEUR	Shimano Dura-Ace 7900
	REAR DERAILLEUR	Shimano Dura-Ace 7900
	BRAKES	Shimano Dura-Ace 7900
	BRAKE LEVERS	Shimano Dura-Ace 7900
	CASSETTE	Shimano Dura-Ace 7900 12x27, 10-speed
	CHAIN	Shimano Dura-Ace 7900
	CRANKSET	Shimano Dura-Ace 7900, 34/50
	BOTTOM BRACKET	Shimano Dura-Ace, Internal Press Fit
WHEELS	RIMS	Shimano Dura-Ace Carbon WH-7850-C24-TL
	HUBS	Shimano Dura-Ace
	SPOKES	Shimano Dura-Ace
	TIRES	Michelin Pro Optimum, 700x25 Folding
	EXTRAS	

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

An Advanced-grade composite frame forms the heart of this aero-sculpted beauty. Laid-up by hand, Defy Advanced adds road-smoothing comfort to aggressive racing performance. Whether you're sprinting for primes or launching a long solo break, Defy Advanced is engineered to let you ride farther, faster.



KEY UPGRADES (FROM DEFY ADVANCED 1)

- Complete 10-speed Shimano Dura-Ace 7900 compact component group
- Lightest Giant Contact SLR composite handlebar and stem
- Highest performance Shimano Dura-Ace Carbon C24 wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS 43.0	385462	71.0	74.0	51.5	12.5	42.0	98.3	29.0
S 46.5	385463	72.0	74.0	53.0	14.5	42.0	99.0	29.8
M 50.0	385464	72.5	73.0	54.5	16.5	42.0	99.0	30.7
M/L 53.5	385465	72.5	73.0	56.0	18.5	42.0	100.5	31.2
L 55.5	385466	72.5	72.0	57.5	20.5	42.0	100.8	31.9
XL 58.5	385467	72.5	72.0	59.5	22.5	42.0	102.8	32.7

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire