

DEFY ALLIANCE 1

CLIMB MOUNTAINS, CARVE THROUGH CORNERS AND EXPERIENCE A PERFORMANCE BIKE WITH FLAWLESS COMFORT AND STABILITY.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,M/L,L,XL
	COLORS	Blue/Composite/White
	FRAME	Alliance Composite/Aluminum Technology
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Connect, 31.8
	STEM	Giant Connect
	SEATPOST	Giant Connect SL Composite, 30.9
	SADDLE	Selle Royal Seta M
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano Tiagra
	FRONT DERAILLEUR	Shimano Tiagra
	REAR DERAILLEUR	Shimano Tiagra
	BRAKES	Tektro Giant specific TK-R710, Dual Pivot
	BRAKE LEVERS	Shimano Tiagra
	CASSETTE	Shimano HG50 12x27, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	FSA Gossamer MegaExo, 34/50
BOTTOM BRACKET	FSA Mega Exo, Internal	
WHEELS	RIMS	Mavic CXP22
	HUBS	Formula sealed Cartridge Bearing 24/28h
	SPOKES	SAPIM Race, 14/15g
	TIRES	Kenda Kriterium, 700x25
EXTRAS		

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

With a redesigned frame blending the best traits of aluminum and composite, the all-new Defy Alliance finds that sweet spot on every ride. With its OverDrive headtube/steerer tube and fork, it tracks beautifully through corners. And its PowerCore bottom bracket area delivers your power straight to the pedals.



FEATURES

- 9-speed Shimano Tiagra drivetrain and FSA Gossamer MegaExo compact crankset
- Giant Connect handlebar and stem
- Mavic CXP22 wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS 43.0	383762	71.0	74.0	51.2	12.5	42.0	99.0	29.2
S 46.5	383763	72.0	74.0	53.1	14.5	42.0	99.1	30.0
M 50.0	383764	72.5	73.0	54.9	16.5	42.0	99.4	30.9
M/L 53.5	383765	72.5	73.0	56.0	18.5	42.0	100.5	31.2
L 55.5	383766	72.5	72.0	57.5	20.0	42.0	102.0	32.1
XL 58.5	383767	72.5	72.5	60.0	22.5	42.0	103.9	32.8

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire