

# DEFY ALLIANCE 0

CLIMB MOUNTAINS, CARVE THROUGH CORNERS AND EXPERIENCE A PERFORMANCE BIKE WITH FLAWLESS COMFORT AND STABILITY.



## SPECIFICATIONS

FRAME	SIZES	XS,S,M,M/L,L,XL	
	COLORS	Red/Composite/White	
	FRAME	Alliance Composite/Aluminum Technology	
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer	
SHOCK		N / A	
COMPONENTS	HANDLEBAR	Giant Connect SL, 31.8	
	STEM	Giant Connect SL	
	SEATPOST	Giant Connect SL Composite, 30.9	
	SADDLE	Fi'zi:k Alliante Delta w/ Manganese rails	
	PEDALS	Not Included	
	DRIVETRAIN	SHIFTERS	Shimano 105
FRONT DERAILLEUR		Shimano 105	
REAR DERAILLEUR		Shimano 105	
BRAKES		Shimano 105	
BRAKE LEVERS		Shimano 105	
CASSETTE		Shimano 105 12x25, 10-speed	
CHAIN		Shimano 105	
CRANKSET		Shimano FC-R600, 34/50	
BOTTOM BRACKET		Shimano Internal	
WHEELS		RIMS	Mavic Aksium Race
	HUBS	Mavic Aksium Race	
	SPOKES	Mavic Aksium Race	
	TIRES	Michelin Lithion, 700x25 Folding	
	EXTRAS		

Specifications and availability subject to change without notice.

## FRAME TECHNOLOGY

With a redesigned frame blending the best traits of aluminum and composite, the all-new Defy Alliance finds that sweet spot on every ride. With its OverDrive headtube/steerer tube and fork, it tracks beautifully through corners. And its PowerCore bottom bracket area delivers your power straight to the pedals.



## KEY UPGRADES (OVER DEFY ALLIANCE 1)

- 9-speed Shimano 105 components with R600 compact crankset
- Giant Connect SL handlebar and stem
- Lightweight Mavic Aksium wheelset

## FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS 43.0	383852	71.0	74.0	51.2	12.5	42.0	99.0	29.2
S 46.5	383853	72.0	74.0	53.1	14.5	42.0	99.1	30.0
M 50.0	383854	72.5	73.0	54.9	16.5	42.0	99.4	30.9
M/L 53.5	383855	72.5	73.0	56.0	18.5	42.0	100.5	31.2
L 55.5	383856	72.5	72.0	57.5	20.0	42.0	102.0	32.1
XL 58.5	383857	72.5	72.5	60.0	22.5	42.0	103.9	32.8

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire