

DEFY ADVANCED 3

RIDE FARTHER AND FASTER. LIKE A PLUSH
FIRST-CLASS SEAT ON A SPEEDING BULLET TRAIN.
FAST, EFFICIENT—AND SILKY SMOOTH.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,M/L,L,XL
	COLORS	Dark Silver/Composite/White
	FRAME	Advanced-Grade Composite
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Connect SL, 31.8
	STEM	Giant Connect SL
	SEATPOST	Giant Vector Composite
	SADDLE	Selle Royal Seta M
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano 105
	FRONT DERAILLEUR	Shimano 105
	REAR DERAILLEUR	Shimano 105
	BRAKES	Tektro Giant specific TK-R710, Dual Pivot
	BRAKE LEVERS	Shimano 105
	CASSETTE	Shimano 105 [Compact 12x25, Triple 12x27], 10-Speed
	CHAIN	Shimano 105
	CRANKSET	FSA Gossamer MegaExo [Compact 34/50, Triple 30/39/50]
	BOTTOM BRACKET	FSA MegaExo, Internal Press Fit
WHEELS	RIMS	Mavic CXP22
	HUBS	Formula sealed Cartridge Bearing 24/28h
	SPOKES	SAPIM Race, 14/15g
	TIRES	Michelin Lithion 2, 700x25 Folding
	EXTRAS	

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

An Advanced-grade composite frame forms the heart of this aero-sculpted beauty. Laid-up by hand, Defy Advanced adds road-smoothing comfort to aggressive racing performance. Whether you're sprinting for primes or launching a long solo break, Defy Advanced is engineered to let you ride farther, faster.



FEATURES

- Available with Compact or Triple FSA Gossamer Crankset
- 10-speed Shimano 105 shifting
- Giant Vector composite seatpost
- Mavic CXP22 wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height**
centimeters	Compact	Triple	degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS 43.0	384552	384652	71.0	74.0	51.5	12.5	42.0	98.3	29.0
S 46.5	384553	384653	72.0	74.0	53.0	14.5	42.0	99.0	29.8
M 50.0	384554	384654	72.5	73.0	54.5	16.5	42.0	99.0	30.7
M/L 53.5	384555	384655	72.5	73.0	56.0	18.5	42.0	100.5	31.2
L 55.5	384556	384656	72.5	72.0	57.5	20.5	42.0	100.8	31.9
XL 58.5	384557	384657	72.5	72.0	59.5	22.5	42.0	102.8	32.7

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire