

RAPID 3

FOR FITNESS, COMMUTING OR JUST PLAIN FUN, RAPID'S BLEND OF FLAT-BAR CONTROL AND ROAD BIKE SPEED IS THE SMART WAY TO GET THERE FASTER.



SPECIFICATIONS

FRAME	SIZES	XS, S, M, L, XL
	COLORS	Silver/White/Black
	FRAME	ALUXX SL-Grade Aluminum
	FORK	CroMo, OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Connect, flat 31.8
	STEM	Alloy adjustable height
	SEATPOST	Giant Connect, 30.9
	SADDLE	Giant Performance Road, Men's
	PEDALS	Caged w/ Clips
DRIVETRAIN	SHIFTERS	Shimano R221 EZ Fire
	FRONT DERAILLEUR	Shimano R443
	REAR DERAILLEUR	Shimano Sora
	BRAKES	Alloy Dual Pivot
	BRAKE LEVERS	Generic Alloy
	CASSETTE	SRAM PG 830 11x28, 8-speed
	CHAIN	KMC Z72
	CRANKSET	FSA Tempo, 30/42/52
	BOTTOM BRACKET	FSA Cartridge
	WHEELS	RIMS
HUBS		[F] Formula Sealed, [R] Shimano 2200, 32h
SPOKES		Stainless Steel
TIRES		Kenda Kwest, 700x28
EXTRAS		Alloy bar-ends

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

It's versatile, it's inviting, and most importantly, it's a bike you'll want to ride every day. With high-quality ALUXX SL aluminum tubing and comfortable, stretched-out flat-bar geometry, Rapid is your ticket to improved fitness or a stress-free commute—or both.



FEATURES

- CroMo fork
- Wide-range 8-speed Shimano shifting with FSA Tempo triple crankset
- Giant Performance Road saddle

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	380062	71.0	74.0	53.5	12.5	42.5	100.8	29.1
S/46.5 cm	380063	72.0	74.0	55.0	14.5	42.5	101.5	30.3
M/50.0 cm	380064	72.5	73.0	56.5	16.5	42.5	101.5	31.0
L/55.5 cm	380065	72.5	73.0	59.5	20.5	42.5	103.3	32.5
XL/58.5 cm	380066	72.5	72.5	61.5	22.5	42.5	105.3	33.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire