

TCX 1

YOUR HEART'S RACING. MUD IS FLYING. THINK FAST, OBSTACLE AHEAD. WHETHER IT'S A 'CROSS RACE OR A VENTURE OFF THE BEATEN PATH, TCX IS READY.



SPECIFICATIONS

FRAME	SIZES	S,M,M/L,L,XL
	COLORS	White/Black/Red
	FRAME	ALUXX SL-Grade Aluminum
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
SHOCK	N / A	
COMPONENTS	HANDLEBAR	Giant Connect SL, 31.8
	STEM	Giant Connect SL
	SEATPOST	Giant Connect SL Composite, 30.9
	SADDLE	Selle Italia Seta M
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	SRAM Rival
	FRONT DERAILLEUR	SRAM Rival
	REAR DERAILLEUR	SRAM Rival
	BRAKES	AVID Shorty 6
	BRAKE LEVERS	SRAM Rival
	CASSETTE	SRAM Force 1070, 12x26, 10-speed
	CHAIN	SRAM PC 1050
	CRANKSET	SRAM Rival, 34/48
	BOTTOM BRACKET	SRAM GXP, External
	WHEELS	RIMS
HUBS		Formula sealed Cartridge Bearing 24/28h
SPOKES		SAPIM Race, 14/15g
TIRES		Kenda Small Block Eight, 700x35 Folding 120TPI
EXTRAS		Top Bar Tektro RL721 cyclocross specific brake lever

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Where Team Rabobank resides, cyclocross is religion. TCX can trace its roots to the cold, damp fields of northern Europe, where Rabobank riders compete at the highest levels of the sport. Super-light ALUXX SL aluminum frames, stable geometry and plenty of mud clearance give you all you need to win.



KEY UPGRADES (FROM TCX 2)

- SRAM Rival drivetrain
- Oversize, lightweight composite fork
- Giant Connect SL bar and stem, Giant Connect SL composite seatpost
- Mavic CXP22 wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
S 49	385083	71.0	73.5	53.5	13.5	43.0	101.9	30.5
M 51.5	385084	72.0	73.0	55.5	15.0	43.0	102.5	31.5
M/L 53.5	385085	72.0	72.0	57.0	17.0	43.0	103.1	32.5
L 55.5	385086	72.0	72.0	58.5	18.5	43.0	104.6	33.1
XL 58.5	385087	72.0	72.0	60.5	20.0	43.0	106.6	34.0

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire