

# TRANCE X ADVANCE SL 0

TOO BEAUTIFUL FOR PUNISHING TRAIL RIDES,  
YOU SAY? NOPE—GORGEOUS AS IT IS, IT'S ALSO  
THE BEST WAY TO TACKLE EPIC OFF-ROAD DAYS.



## SPECIFICATIONS

FRAME	SIZES	S,M,L,XL
	COLORS	Composite/White
	FRAME	Advanced SL-Grade Composite, 5" Maestro Suspension
	FORK	Fox 32 Talas FIT RLC w/ 15QR Thru Axle and tapered steerer, 100-140 mm travel
SHOCK		Fox Float RP23
COMPONENTS	HANDLEBAR	Giant Contact SLR, Composite, low rise 31.8
	STEM	Giant Contact SLR, Composite
	SEATPOST	Giant Contact SLR, Composite, 30.9
	SADDLE	Fizik Gobi XM w/ Braided Composite rails
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano XTR
	FRONT DERAILLEUR	Shimano XTR
	REAR DERAILLEUR	Shimano XTR Shadow, top normal
	BRAKES	Avid Elixir CR Mag, 185F/160R
	BRAKE LEVERS	Avid Elixir Mag
	CASSETTE	Shimano XTR 11x34, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	Race Face Next SL Carbon, 22/32/44
BOTTOM BRACKET		Race Face, External
WHEELS	RIMS	Mavic CrossMax ST
	HUBS	Mavic CrossMax ST w/ 15mm Front Axle
	SPOKES	Mavic CrossMax ST
	TIRES	Kenda Nevegal, 26x2.1 Folding
	EXTRAS	

Specifications and availability subject to change without notice.

## FRAME TECHNOLOGY

Bolstered by 5 inches of super-stable Maestro suspension and an all-new, meticulously engineered Advanced SL-grade composite frame, this is the lightest, fastest way to tame any trail. Climb faster, descend with more confidence, and squeeze the most out of every singletrack adventure.



## KEY UPGRADES (OVER TRANCE X ADVANCED SL 1)

- Fox 32 Talas FIT F120RL, 120mm tapered suspension fork, Fox Float RP23 rear shock
- Shimano XTR drivetrain/shifting with Avid Elixir CR Mag disc brakes and Race Face Next SL carbon crankset
- Giant Contact SLR handlebar, stem and seatpost
- Mavic CrossMax ST Disc wheelsset

## FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
inches		degrees	degrees	inches	inches	inches	inches	inches
S 16	348053	69.5	73.5	22.0	5.1	17.1	42.6	28.5
M 18	348054	69.5	73.5	23.0	5.7	17.1	43.6	30.0
L 20	348055	69.5	73.5	24.0	6.5	17.1	44.6	31.2
XL 22	348056	69.5	73.5	25.0	6.9	17.1	45.7	32.4

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire