

# TRANCE X2

IT'S SIMPLE: THE FASTER YOU RIDE, THE MORE TRAILS YOU'LL CONQUER. CLIMB HIGHER, DESCEND MORE. AND DO IT ALL WITH JUST ONE BIKE.



## SPECIFICATIONS

FRAME	SIZES	XS,S,M,L,XL
	COLORS	Satin Gray/Orange
	FRAME	ALUXX SL-Grade Aluminum, 5" Maestro Suspension
	FORK	Fox 32 F120RL w/ 15QR Thru Axle, 120mm travel
SHOCK	Fox Float RP2	
COMPONENTS	HANDLEBAR	Giant Connect SL, low rise 31.8
	STEM	Giant Connect SL
	SEATPOST	Giant Connect SL, 30.9
	SADDLE	Fi'zi:k Gobi XM w/ Manganese rails
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano Deore XT
	FRONT DERAILLEUR	Shimano SLX
	REAR DERAILLEUR	Shimano Deore XT Shadow, top normal
	BRAKES	Avid Elixir 5 185F/160R
	BRAKE LEVERS	Avid Elixir 5
	CASSETTE	SRAM PG-980 11x34, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	Shimano SLX, 22/32/44
BOTTOM BRACKET	Shimano SLX, external	
WHEELS	RIMS	WTB LaserDisc Trail
	HUBS	[F] Giant Tracker Sealed/CNC w/ 15mm Axle, [R] Shimano Deore, 32h
	SPOKES	DT Competition, 14/15g
	TIRES	Kenda Nevegal, 26x2.1 Folding
	EXTRAS	

Specifications and availability subject to change without notice.

## FRAME TECHNOLOGY

A perfectly balanced ALUXX SL aluminum frame—bolstered with 5 inches of fully active Maestro suspension travel—will keep you rolling through technical terrain, blitzing descents and devouring steep climbs. Ride more trails. And ride them faster.



## KEY UPGRADES (OVER TRANCE X3)

- Fox 32 F120RL, 120mm suspension fork w/ 15QR thru-axle, Fox Float RP2 rear shock
- Shimano Deore XT shifting, Avid Elixir 5 hydraulic disc brakes
- Giant Connect SL handlebar, stem and seatpost
- WTB LaserDisc Trail rim/Giant Tracker hub/Shimano Deore hub/DT Competition spokes, wheelset

## FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height**
inches		degrees	degrees	inches	inches	inches	inches	inches
XS 14.5	345052	69.5	73.5	21.5	4.7	17.1	41.9	30.5
S 16	345053	69.5	73.5	22.0	5.1	17.1	42.6	30.9
M 18	345054	69.5	73.5	23.0	5.7	17.1	43.6	31.4
L 20	345055	69.5	73.5	24.0	6.5	17.1	44.6	32.0
XL 22	345056	69.5	73.5	25.0	7.5	17.1	45.7	32.4

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire