

# XTC 29ER 1

ROLL THROUGH THE STICKEST TRAIL SITUATIONS WITH CONFIDENCE AND CONTROL. THE BENEFITS OF LARGER WHEELS WITHOUT COMPROMISE.



## SPECIFICATIONS

FRAME	SIZES	S,M,L,XL
	COLORS	Black/Blue
	FRAME	ALUXX SL-Grade Aluminum
	FORK	FOX 32 F29 RL-100 w/15QR Thru Axle and tapered steerer, 100mm travel
SHOCK	N / A	
COMPONENTS	HANDLEBAR	Giant Contact, flat 31.8
	STEM	Giant Connect SL
	SEATPOST	Giant Connect SL, 30.9
	SADDLE	Fi'zi:k Tundra w/ Manganese rails
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano SLX
	FRONT DERAILLEUR	Shimano Deore
	REAR DERAILLEUR	Shimano Deore XT Shadow, top normal
	BRAKES	Avid Juicy 3 160mm
	BRAKE LEVERS	Avid Juicy 3
	CASSETTE	Shimano HG61 12x36, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	Shimano Deore, 22/32/44
	BOTTOM BRACKET	Shimano Deore, External
WHEELS	RIMS	Giant P29, ALUXX Double wall alloy*
	HUBS	[F] Giant Tracker Sealed w/ 15mm Axle, [R] Shimano Deore, 32h
	SPOKES	Stainless Steel, 14g
	TIRES	Kenda Karma, 29x2.0 Folding
	EXTRAS	*Rims design is compatible with aftermarket tubeless conversion systems

Specifications and availability subject to change without notice.

## FRAME TECHNOLOGY

The all-new Xtc 29er brings precise trail-handling and agility to the world of 29-inch wheels. With highly engineered ALUXX SL aluminum tubing and performance XC geometry (60mm BB drop with 305mm BB height), it has both predictable stability and surprising snappiness. Add in Giant's all-new, ultra-stiff P29 rim and 29er-specific flat handlebar, and it's the ideal way to tackle any racecourse or weekend epic.



### KEY UPGRADES (OVER XTC 29ER 2)

- Fox 32 F29 RL-100, 15mm thru-axle, tapered steerer fork
- Shimano Deore crankset, Shimano Deore XT Shadow rear derailleur
- Fi'zi:k Tundra saddle w/ Manganese rails
- Avid Juicy 3 disc brakes

## FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
inches		degrees	degrees	inches	inches	inches	inches	inches
S 16	333873	71.0	73.0	22.4	3.5	17.3	41.8	28.5
M 18	333874	71.5	72.5	23.4	3.9	17.3	42.4	29.6
L 20	333875	71.5	72.5	24.2	3.9	17.3	43.2	30.5
XL 22	333876	71.5	72.5	25.0	4.7	17.3	44.0	31.6

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire