

## DEFY ADVANCED 1

Introducing the all-new Defy Advanced. Lighter, stiffer, more aggressive high-performance, from the composite technology leader. Aero speed meets the road-smoothing ride of a perfectly engineered composite structure. It's go-fast versatility, for the club ride or race day.



## SPECIFICATIONS

FRAME	SIZES	XS,S,M,M/L,L,XL
	COLORS	Red/Silver/Composite
	FRAME	Advanced-Grade Composite
	FORK	Advanced-Grade Composite, Full Composite OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Race Face Revolution, 31.8
	STEM	Race Face Revolution
	SEATPOST	Vector Composite Seatpost
	SADDLE	Fi'zi:k Aliante Delta w/ Manganese rails
	PEDALS	Crank Brothers Smarty
DRIVETRAIN	SHIFTERS	Shimano Ultegra
	FRONT DERAILLEUR	Shimano Ultegra
	REAR DERAILLEUR	Shimano Dura-Ace
	BRAKES	Shimano Ultegra
	BRAKE LEVERS	Shimano Ultegra
	CASSETTE	Shimano Ultegra 12/27, 10-speed
	CHAIN	Shimano Ultegra
	CRANKSET	Shimano Ultegra compact, 34/50*
	BOTTOM BRACKET	Shimano Dura-Ace, Internal Press Fit
	WHEELS	RIMS
HUBS		Mavic Ksyrium Elite
SPOKES		Mavic Ksyrium Elite
TIRES		Michelin Pro Race3, 700x25 Folding
EXTRAS		

## FRAME TECHNOLOGY

Advanced-grade composite ensures precise frame alignment and structural perfection, with aero sculpted main tubes and a new Vector aero seatpost to give you every edge on those solo efforts. Ride-tuned composite layout and endurance position geometry let you ride longer and stronger than ever before.



## KEY UPGRADES (FROM DEFY ADVANCED 2)

- 10-speed Shimano Ultegra/Dura-Ace components
- Lightest Race Face Revolution handlebar and stem
- Lightest Mavic Ksyrium Elite wheelset

## FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	384442	71.0	74.0	51.5	12.5	42.0	98.3	29.0
S/46.5 cm	384443	72.0	74.0	53.0	14.5	42.0	99.0	29.8
M/50.0 cm	384444	72.5	73.0	54.5	16.5	42.0	99.0	30.7
M/L/53.5 cm	384445	72.5	73.0	56.0	18.5	42.0	100.5	31.2
L/55.5 cm	384446	72.5	72.0	57.5	20.5	42.0	100.8	31.9
XL/58.5 cm	384447	72.5	72.0	59.5	22.5	42.0	102.8	32.7

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire