

TCR ADVANCED SL 1

SOLO ATTACKS. SPRINT WINS. CHAMPAGNE AND PODIUMS. THIS IS THE BIKE OF CHOICE FOR GIRO D'ITALIA CHAMPION DENIS MENCHOV AND TEAM RABOBANK. IF WINNING MATTERS MOST, MAKE IT YOUR CHOICE, TOO.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,L,XL
	COLORS	Composite/White
	FRAME	Advanced SL-Grade Composite, Integrated Seatpost
	FORK	Advanced SL-Grade Composite, Full Composite OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Contact SLR, Composite, 31.8
	STEM	Giant Contact SLR, Composite
	SEATPOST	Advanced SL-Grade Composite, Integrated Design
	SADDLE	Fi'zi:k Arione CX w/ Braided Composite rails
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	SRAM Red
	FRONT DERAILLEUR	SRAM Red
	REAR DERAILLEUR	SRAM Red
	BRAKES	SRAM Red
	BRAKE LEVERS	SRAM Red
	CASSETTE	SRAM RED 1090 11x25, 10-speed
	CHAIN	SRAM PC 1090
	CRANKSET	SRAM RED, 39/53
	BOTTOM BRACKET	SRAM GXP, Internal Press Fit
WHEELS	RIMS	Mavic Cosmic Carbone SL, Clincher
	HUBS	Mavic Cosmic Carbone SL
	SPOKES	Mavic Cosmic Carbone SL
	TIRES	Michelin Pro3 Race, 700x23, Folding
	EXTRAS	2 ISP clamps provided: Regular 20mm & XL 45mm

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

No other road bike in the world comes closer to the holy trinity of light weight, pedaling stiffness and compliance. Featuring the highest-performance Advanced SL-grade composite, meticulous hand-crafted construction and benchmark features, including an integrated seatmast and massive MegaDrive downtube, it's built to win.



KEY UPGRADES (FROM TCR ADVANCED SL 2)

- SRAM Red component group
- Fi'zi:k Arione CX composite-rail saddle
- Mavic Cosmic Carbone SL wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS 43.0	387052	71.0	74.5	52.0	12.0	40.5	97.7	28.5
S 46.5	387053	72.0	73.5	53.5	13.5	40.5	97.4	29.2
M 50.0	387054	73.0	73.0	55.5	15.0	40.5	98.0	30.1
M/L 53.5	387055	73.0	72.0	57.0	17.0	40.5	98.6	31.0
L 55.5	387056	73.0	72.0	58.5	18.5	40.5	100.1	31.7
XL 58.5	387057	73.0	72.0	60.5	20.0	40.5	102.1	32.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire