

# ROAM 1

THE ROAD TO ADVENTURE IS SELDOM SMOOTH. EMBRACE THE UNKNOWN AND ROAM A LITTLE WITH A BIKE THAT'S READY FOR ANYTHING.



## SPECIFICATIONS

FRAME	SIZES	S, M, L, XL
	COLORS	White/Red
	FRAME	ALUXX-Grade Aluminum
	FORK	SR Suntour NEX 4610 w/ Lock-out, 63mm Travel
SHOCK		N/A
COMPONENTS	HANDLEBAR	Giant Sport Alloy, 30mm rise, 25.4
	STEM	Giant Sport Alloy
	SEATPOST	Giant Sport Alloy, 30.9
	SADDLE	Giant X-Road Sport Men's
	PEDALS	VP-992S steel cage
DRIVETRAIN	SHIFTERS	SRAM X.5 Trigger
	FRONT DERAILEUR	Shimano Altus
	REAR DERAILEUR	SRAM X.5
	BRAKES	Avid BB5 Disc
	BRAKE LEVERS	Tektro 3-Finger w/Kraton Comfort Grip
	CASSETTES	SRAM PG830 11x32, 8-speed
	CHAIN	KMC Z72NP
	CRANKSET	Shimano M361, 28/38/48
	BOTTOM BRACKET	Sealed Cartridge
	WHEELS	RIMS
HUBS		Alloy Sealed, 32h w/ QR
SPOKES		Stainless Steel
TIRES		Kenda Kwick, 700x40
EXTRAS		

## FRAME TECHNOLOGY

Designed around a lightweight, strong and reliable ALUXX aluminum frame and fast-rolling 700c diameter wheels, Roam is eager to go the distance. With a suspension fork that smoothes out rough trails—and can be locked out on smooth roads—plus disc brakes and clearance for large tires, you'll learn to love detours.



### KEY UPGRADES (OVER ROAM 2)

- SRAM X.5 trigger shifting
- Avid BB5 disc brakes
- Giant Sport Alloy rims, disc specific

## FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
Inches		Degrees	Degrees	Inches	Inches	Inches	Inches	Inches
S/17	354413	71.0	73.0	22.5	4.3	17.6	41.9	30.0
M/19	354414	71.0	73.0	22.8	4.5	17.6	42.6	30.9
L/21	354415	71.0	73.0	23.5	4.7	17.6	43.2	32.0
XL/23	354416	71.0	73.0	24.0	4.9	17.6	44.0	33.1

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire